















CFP2000 Result

Copyright ©1999-2000, Standard Performance Evaluation Corporation

SPECfp2000 = 3368

SPECfp_base2000 = 3162

SPEC license #00407 Tested by: Vladimir Makarov Test date: Dec 18, 2018 Hardware Avail: Now Software Avail: Now

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	54.3	2945	58.5	2737	
171.swim	3100	53.8	5764	52.7	5885	
172.mgrid	1800	115	1568	111	1621	
173.applu	2100	98.4	2134	74.3	2826	
177.mesa	1400	64.7	2164	61.7	2268	
178.galgel	2900	49.0	5913	47.1	6154	
179.art	2600	46.0	5649	41.2	6315	
183.earth	1300	32.6	3984	26.6	4885	
187.facerec	1900	50.9	3733	50.9	3729	
188.amp	2200	81.9	2687	81.8	2691	
189.lucas	2000	32.5	6149	32.4	6177	
191.fma3d	2100	73.4	2860	63.9	3286	
200.sixtrack	1100	75.3	1461	75.0	1466	
301.apsi	2600	110	2367	102	2543	

Hardware

CPU:
CPU MHz:
FPU: Integrated
CPU(s) enabled: 12
CPU(s) orderable:
Parallel: No
Primary Cache:
Secondary Cache:
L3 Cache:
Other Cache:
Memory: 13055488 kB
Disk Subsystem:
Other Hardware:

Software

Operating System: Linux 3.10.0-229.el7.ppc64
Compiler: gcc version 9.0.0 20181218 (experimental) (GCC)
File System:
System State: multiuser

Notes/Tuning Information

Base flags: -O2 -m32 -mtune=power7
Peak flags: -O3 -m32 -mtune=power7

Errors

'reportable' flag not set during run