CFP2000 Result

Copyright ©1999-2000, Standard Performance Evaluation Corporation

--

SPECfp2000 = 1173

SPECfp_base2000 = 1062

SPEC license #00407	Tested by: Vladimir Makarov	Test date: May 31, 2017	Hardware Avail: Now	Software Avail: Now

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	150	1068	99.3	1611
171.swim	3100	337	919	329	944
172.mgrid	1800	333	541	257	700
173.applu	2100	226	931	192	1092
177.mesa	1400	93.1	1503	92.0	1522
178.galgel	2900	131	2221	126	2301
179.art	2600	136	1916	129	2022
183.equake	1300	173	750	160	813
187.facerec	1900	174	1095	122	1552
188.ammp	2200	237	928	226	973
189.lucas	2000	127	1578	121	1659
191.fma3d	2100	190	1103	195	1075
200.sixtrack	1100	199	554	240	459
301.apsi	2600	260	998	230	1130



Hardware

CPU:	ARMv7Processorrev3(v7l)
CPU MHz:	
FPU:	Integrated
CPU(s) enabled:	8
CPU(s) orderable:	
Parallel:	No
Primary Cache:	
Secondary Cache:	
L3 Cache:	
Other Cache:	
Memory:	2038764kB
Disk Subsystem:	
Other Hardware:	

Software

Operating System:	Linux 3.10.82-39
Compiler:	gcc version 8.0.0 20170601 (experimental) (GCC)
File System:	
System State:	multiuser

Notes/Tuning Information

```
Base flags: -O2
Peak flags: -Ofast -flto -mtune=native
```

Errors

'reportable' flag not set during run

Invalid Run