

# CFP2000 Result

Copyright ©1999-2000, Standard Performance Evaluation Corporation

SPECfp2000 = 2283

SPECfp\_base2000 = 1982

SPEC license #00407 Tested by: Vladimir Makarov Test date: Jun 21, 2021 Hardware Avail: Now Software Avail: Now

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	84.7	1889	63.7	2512	
171.swim	3100	129	2401	136	2284	
172.mgrid	1800	113	1598	126	1429	
173.applu	2100	162	1296	146	1441	
177.mesa	1400	54.5	2567	56.7	2469	
178.galgel	2900	65.4	4436	53.8	5391	
179.art	2600	44.1	5896	33.9	7667	
183.quake	1300	69.3	1877	65.4	1987	
187.facerec	1900	110	1729	58.5	3245	
188.amp	2200	119	1853	109	2015	
189.lucas	2000	104	1921	101	1978	
191.fma3d	2100	151	1387	X	X	
200.sixtrack	1100	113	971	113	973	
301.apsi	2600	177	1469	172	1515	

## Hardware

CPU: Genuine Intel(R) CPU @ 2.66GHz  
CPU MHz: 2666.461  
FPU: Integrated  
CPU(s) enabled: 4  
CPU(s) orderable: No  
Parallel: No  
Primary Cache:  
Secondary Cache: 4096 KB  
L3 Cache:  
Other Cache:  
Memory: 4036100 kB  
Disk Subsystem:  
Other Hardware:

## Software

Operating System: Linux 5.1.16-200.fc29.x86\_64  
Compiler: gcc version 12.0.0 20210621 (experimental) (GCC)  
File System:  
System State: multiuser

## Notes/Tuning Information

Base flags: -O2 -mtune=generic  
Peak flags: -Ofast -flto

## Errors

'reportable' flag not set during run  
191.fma3d peak did not have enough runs!