















# CFP2000 Result

Copyright ©1999-2000, Standard Performance Evaluation Corporation

SPECfp2000 = 2250

SPECfp\_base2000 = 1996

SPEC license #00407 Tested by: Vladimir Makarov Test date: Jun 24, 2021 Hardware Avail: Now Software Avail: Now

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	82.8	1933	63.7	2511	
171.swim	3100	129	2401	136	2284	
172.mgrid	1800	113	1598	126	1427	
173.applu	2100	162	1297	146	1434	
177.mesa	1400	54.4	2575	56.9	2460	
178.galgel	2900	65.4	4434	53.7	5403	
179.art	2600	41.5	6264	34.3	7587	
183.equake	1300	69.3	1875	65.4	1986	
187.facerec	1900	110	1732	58.5	3251	
188.amp	2200	118	1870	109	2023	
189.lucas	2000	104	1921	101	1975	
191.fma3d	2100	152	1385	111	1894	
200.sixtrack	1100	113	973	113	972	
301.apsi	2600	177	1470	172	1514	

## Hardware

CPU: Genuine Intel(R) CPU @ 2.66GHz  
CPU MHz: 2666.489  
FPU: Integrated  
CPU(s) enabled: 4  
CPU(s) orderable: No  
Parallel: No  
Primary Cache:  
Secondary Cache: 4096 KB  
L3 Cache:  
Other Cache:  
Memory: 4036100 kB  
Disk Subsystem:  
Other Hardware:

## Software

Operating System: Linux 5.1.16-200.fc29.x86\_64  
Compiler: gcc version 12.0.0 20210624 (experimental) (GCC)  
File System:  
System State: multiuser

## Notes/Tuning Information

Base flags: -O2 -mtune=generic  
Peak flags: -Ofast -flto

## Errors

'reportable' flag not set during run