

# CFP2000 Result

Copyright ©1999-2000, Standard Performance Evaluation Corporation

SPECfp2000 = 2255

SPECfp\_base2000 = 1995

SPEC license #00407 Tested by: Vladimir Makarov Test date: Jun 25, 2021 Hardware Avail: Now Software Avail: Now

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	83.4	1919	63.7	2511	
171.swim	3100	129	2402	136	2283	
172.mgrid	1800	113	1598	126	1429	
173.applu	2100	162	1295	147	1433	
177.mesa	1400	54.4	2574	55.4	2528	
178.galgel	2900	65.4	4436	53.8	5390	
179.art	2600	41.5	6260	34.1	7633	
183.equake	1300	69.4	1873	65.5	1986	
187.facerec	1900	110	1731	58.5	3249	
188.amp	2200	118	1872	109	2023	
189.lucas	2000	104	1922	101	1973	
191.fma3d	2100	151	1386	111	1897	
200.sixtrack	1100	113	972	113	975	
301.apsi	2600	177	1470	172	1514	

## Hardware

CPU: Genuine Intel(R) CPU @ 2.66GHz  
CPU MHz: 2666.487  
FPU: Integrated  
CPU(s) enabled: 4  
CPU(s) orderable: No  
Parallel: No  
Primary Cache:  
Secondary Cache: 4096 KB  
L3 Cache:  
Other Cache:  
Memory: 4036100 kB  
Disk Subsystem:  
Other Hardware:

## Software

Operating System: Linux 5.1.16-200.fc29.x86\_64  
Compiler: gcc version 12.0.0 20210625 (experimental) (GCC)  
File System:  
System State: multiuser

## Notes/Tuning Information

Base flags: -O2 -mtune=generic  
Peak flags: -Ofast -flto

## Errors

'reportable' flag not set during run