

CFP2000 Result

Copyright ©1999-2000, Standard Performance Evaluation Corporation

SPECfp2000 = 2251

SPECfp_base2000 = 1998

SPEC license #00407 Tested by: Vladimir Makarov Test date: Jul 01, 2021 Hardware Avail: Now Software Avail: Now

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	83.3	1922	63.7	2511	
171.swim	3100	129	2403	136	2285	
172.mgrid	1800	113	1598	126	1428	
173.applu	2100	162	1297	146	1434	
177.mesa	1400	54.4	2572	55.4	2527	
178.galgel	2900	65.4	4437	53.8	5394	
179.art	2600	41.0	6347	35.0	7431	
183.equake	1300	69.4	1875	65.4	1987	
187.facerec	1900	110	1734	58.6	3244	
188.amp	2200	118	1871	109	2022	
189.lucas	2000	104	1930	101	1978	
191.fma3d	2100	151	1387	111	1891	
200.sixtrack	1100	113	972	113	973	
301.apsi	2600	177	1471	172	1515	

Hardware

CPU: Genuine Intel(R) CPU @ 2.66GHz
CPU MHz: 2666.489
FPU: Integrated
CPU(s) enabled: 4
CPU(s) orderable: No
Parallel: No
Primary Cache:
Secondary Cache: 4096 KB
L3 Cache:
Other Cache:
Memory: 4036100 kB
Disk Subsystem:
Other Hardware:

Software

Operating System: Linux 5.1.16-200.fc29.x86_64
Compiler: gcc version 12.0.0 20210701 (experimental) (GCC)
File System:
System State: multiuser

Notes/Tuning Information

Base flags: -O2 -mtune=generic
Peak flags: -Ofast -flto

Errors

'reportable' flag not set during run