















CFP2000 Result

Copyright ©1999-2000, Standard Performance Evaluation Corporation

SPECfp2000 = 2254

SPECfp_base2000 = 1993

SPEC license #00407 Tested by: Vladimir Makarov Test date: Jul 03, 2021 Hardware Avail: Now Software Avail: Now

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	83.8	1910	63.7	2511	
171.swim	3100	129	2402	136	2283	
172.mgrid	1800	113	1598	126	1428	
173.applu	2100	162	1297	146	1434	
177.mesa	1400	54.4	2572	55.5	2524	
178.galgel	2900	65.4	4436	53.8	5387	
179.art	2600	41.9	6210	34.3	7591	
183.equake	1300	69.4	1874	65.4	1988	
187.facerec	1900	110	1735	58.5	3247	
188.amp	2200	118	1866	109	2026	
189.lucas	2000	104	1924	101	1976	
191.fma3d	2100	151	1388	111	1896	
200.sixtrack	1100	113	972	113	973	
301.apsi	2600	177	1471	172	1514	

Hardware

CPU: Genuine Intel(R) CPU @ 2.66GHz
CPU MHz: 2666.512
FPU: Integrated
CPU(s) enabled: 4
CPU(s) orderable: No
Parallel: No
Primary Cache:
Secondary Cache: 4096 KB
L3 Cache:
Other Cache:
Memory: 4036100 kB
Disk Subsystem:
Other Hardware:

Software

Operating System: Linux 5.1.16-200.fc29.x86_64
Compiler: gcc version 12.0.0 20210703 (experimental) (GCC)
File System:
System State: multiuser

Notes/Tuning Information

Base flags: -O2 -mtune=generic
Peak flags: -Ofast -flto

Errors

'reportable' flag not set during run