

CFP2000 Result

Copyright ©1999-2000, Standard Performance Evaluation Corporation

SPECfp2000 = 2258

SPECfp_base2000 = 1996

SPEC license #00407 Tested by: Vladimir Makarov Test date: Jul 04, 2021 Hardware Avail: Now Software Avail: Now

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	82.7	1934	63.7	2512	
171.swim	3100	129	2401	136	2284	
172.mgrid	1800	113	1599	126	1428	
173.applu	2100	162	1297	147	1433	
177.mesa	1400	54.4	2575	55.3	2530	
178.galgel	2900	65.3	4442	53.7	5399	
179.art	2600	41.6	6247	33.6	7736	
183.quake	1300	69.3	1875	65.4	1987	
187.facerec	1900	110	1733	58.4	3253	
188.amp	2200	118	1869	109	2023	
189.lucas	2000	104	1923	101	1975	
191.fma3d	2100	151	1388	111	1892	
200.sixtrack	1100	113	971	113	974	
301.apsi	2600	177	1469	172	1515	

Hardware

CPU: Genuine Intel(R) CPU @ 2.66GHz
CPU MHz: 2666.504
FPU: Integrated
CPU(s) enabled: 4
CPU(s) orderable: No
Parallel: No
Primary Cache:
Secondary Cache: 4096 KB
L3 Cache:
Other Cache:
Memory: 4036100 kB
Disk Subsystem:
Other Hardware:

Software

Operating System: Linux 5.1.16-200.fc29.x86_64
Compiler: gcc version 12.0.0 20210704 (experimental) (GCC)
File System:
System State: multiuser

Notes/Tuning Information

Base flags: -O2 -mtune=generic
Peak flags: -Ofast -flto

Errors

'reportable' flag not set during run