















# CFP2000 Result

Copyright ©1999-2000, Standard Performance Evaluation Corporation

SPECfp2000 = 2254

SPECfp\_base2000 = 1995

SPEC license #00407 Tested by: Vladimir Makarov Test date: Jul 05, 2021 Hardware Avail: Now Software Avail: Now

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	82.7	1935	63.7	2512	
171.swim	3100	129	2401	136	2283	
172.mgrid	1800	113	1598	126	1428	
173.applu	2100	162	1296	147	1433	
177.mesa	1400	54.3	2577	55.3	2530	
178.galgel	2900	65.5	4426	53.7	5402	
179.art	2600	41.7	6228	34.3	7585	
183.equake	1300	69.4	1873	65.4	1987	
187.facerec	1900	110	1732	58.5	3248	
188.ammmp	2200	118	1872	109	2024	
189.lucas	2000	104	1924	101	1975	
191.fma3d	2100	151	1387	111	1892	
200.sixtrack	1100	113	971	113	973	
301.apsi	2600	177	1470	172	1515	

## Hardware

CPU: Genuine Intel(R) CPU @ 2.66GHz  
CPU MHz: 2666.489  
FPU: Integrated  
CPU(s) enabled: 4  
CPU(s) orderable: No  
Parallel: No  
Primary Cache:  
Secondary Cache: 4096 KB  
L3 Cache:  
Other Cache:  
Memory: 4036100 kB  
Disk Subsystem:  
Other Hardware:

## Software

Operating System: Linux 5.1.16-200.fc29.x86\_64  
Compiler: gcc version 12.0.0 20210705 (experimental) (GCC)  
File System:  
System State: multiuser

## Notes/Tuning Information

Base flags: -O2 -mtune=generic  
Peak flags: -Ofast -flto

## Errors

'reportable' flag not set during run