















CFP2000 Result

Copyright ©1999-2000, Standard Performance Evaluation Corporation

SPECfp2000 = 2253

SPECfp_base2000 = 1998

SPEC license #00407 Tested by: Vladimir Makarov Test date: Jul 08, 2021 Hardware Avail: Now Software Avail: Now

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	83.4	1920	63.7	2511	
171.swim	3100	129	2402	136	2283	
172.mgrid	1800	113	1598	126	1429	
173.applu	2100	162	1297	146	1434	
177.mesa	1400	54.6	2564	55.4	2526	
178.galgel	2900	65.4	4435	53.9	5383	
179.art	2600	40.7	6384	34.2	7603	
183.equake	1300	69.4	1874	65.4	1987	
187.facerec	1900	109	1737	58.8	3233	
188.amp	2200	118	1871	109	2023	
189.lucas	2000	104	1924	101	1976	
191.fma3d	2100	151	1393	111	1895	
200.sixtrack	1100	113	973	113	973	
301.apsi	2600	177	1470	172	1514	

Hardware

CPU: Genuine Intel(R) CPU @ 2.66GHz
CPU MHz: 2666.473
FPU: Integrated
CPU(s) enabled: 4
CPU(s) orderable: No
Parallel: No
Primary Cache:
Secondary Cache: 4096 KB
L3 Cache:
Other Cache:
Memory: 4036100 kB
Disk Subsystem:
Other Hardware:

Software

Operating System: Linux 5.1.16-200.fc29.x86_64
Compiler: gcc version 12.0.0 20210708 (experimental) (GCC)
File System:
System State: multiuser

Notes/Tuning Information

Base flags: -O2 -mtune=generic
Peak flags: -Ofast -flto

Errors

'reportable' flag not set during run