

# CFP2000 Result

Copyright ©1999-2000, Standard Performance Evaluation Corporation

SPECfp2000 = 2076

SPECfp\_base2000 = 1725

SPEC license #00407 Tested by: Vladimir Makarov Test date: Jun 15, 2021 Hardware Avail: Now Software Avail: Now

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	95.8	1670	76.3	2096	
171.swim	3100	129	2403	138	2245	
172.mgrid	1800	170	1060	147	1228	
173.applu	2100	158	1329	146	1438	
177.mesa	1400	116	1205	64.8	2160	
178.galgel	2900	70.1	4136	61.9	4688	
179.art	2600	42.7	6088	36.7	7077	
183.quake	1300	63.1	2060	60.1	2162	
187.facerec	1900	111	1712	65.6	2897	
188.amp	2200	151	1461	135	1624	
189.lucas	2000	124	1619	106	1885	
191.fma3d	2100	146	1437	124	1700	
200.sixtrack	1100	153	719	112	987	
301.apsi	2600	186	1398	181	1438	

## Hardware

CPU: Genuine Intel(R) CPU @ 2.66GHz  
CPU MHz: 2666.457  
FPU: Integrated  
CPU(s) enabled: 4  
CPU(s) orderable: No  
Parallel: No  
Primary Cache:  
Secondary Cache: 4096 KB  
L3 Cache:  
Other Cache:  
Memory: 4036100 kB  
Disk Subsystem:  
Other Hardware:

## Software

Operating System: Linux 5.1.16-200.fc29.x86\_64  
Compiler: gcc version 12.0.0 20210615 (experimental) (GCC)  
File System:  
System State: multiuser

## Notes/Tuning Information

Base flags: -O2 -mtune=generic -m32  
Peak flags: -Ofast -flto -m32

## Errors

'reportable' flag not set during run