

# CFP2000 Result

Copyright ©1999-2000, Standard Performance Evaluation Corporation

SPECfp2000 = 2078

SPECfp\_base2000 = 1724

SPEC license #00407 Tested by: Vladimir Makarov Test date: Jun 16, 2021 Hardware Avail: Now Software Avail: Now

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	96.1	1664	76.3	2098	
171.swim	3100	129	2402	138	2250	
172.mgrid	1800	170	1060	147	1228	
173.applu	2100	158	1328	146	1437	
177.mesa	1400	116	1206	65.1	2149	
178.galgel	2900	70.3	4123	62.0	4678	
179.art	2600	43.0	6053	35.8	7269	
183.quake	1300	63.1	2060	60.1	2163	
187.facerec	1900	111	1717	65.6	2897	
188.amp	2200	150	1462	135	1624	
189.lucas	2000	123	1620	106	1886	
191.fma3d	2100	146	1438	124	1688	
200.sixtrack	1100	153	721	111	989	
301.apsi	2600	186	1397	181	1436	

## Hardware

CPU: Genuine Intel(R) CPU @ 2.66GHz  
CPU MHz: 2666.467  
FPU: Integrated  
CPU(s) enabled: 4  
CPU(s) orderable: No  
Parallel: No  
Primary Cache:  
Secondary Cache: 4096 KB  
L3 Cache:  
Other Cache:  
Memory: 4036100 kB  
Disk Subsystem:  
Other Hardware:

## Software

Operating System: Linux 5.1.16-200.fc29.x86\_64  
Compiler: gcc version 12.0.0 20210616 (experimental) (GCC)  
File System:  
System State: multiuser

## Notes/Tuning Information

Base flags: -O2 -mtune=generic -m32  
Peak flags: -Ofast -flto -m32

## Errors

'reportable' flag not set during run