

# CFP2000 Result

Copyright ©1999-2000, Standard Performance Evaluation Corporation

SPECfp2000 = 2067

SPECfp\_base2000 = 1725

SPEC license #00407 Tested by: Vladimir Makarov Test date: Jun 25, 2021 Hardware Avail: Now Software Avail: Now

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	95.9	1669	76.4	2095	
171.swim	3100	129	2401	138	2247	
172.mgrid	1800	170	1060	147	1229	
173.applu	2100	158	1329	159	1318	
177.mesa	1400	117	1201	64.2	2181	
178.galgel	2900	69.9	4148	62.0	4679	
179.art	2600	42.7	6087	35.8	7262	
183.equake	1300	63.2	2058	60.1	2163	
187.facerec	1900	111	1708	65.7	2893	
188.amp	2200	149	1475	135	1631	
189.lucas	2000	124	1616	106	1890	
191.fma3d	2100	146	1440	124	1689	
200.sixtrack	1100	153	717	112	982	
301.apsi	2600	186	1397	181	1438	

## Hardware

CPU: Genuine Intel(R) CPU @ 2.66GHz  
CPU MHz: 2666.489  
FPU: Integrated  
CPU(s) enabled: 4  
CPU(s) orderable: No  
Parallel: No  
Primary Cache:  
Secondary Cache: 4096 KB  
L3 Cache:  
Other Cache:  
Memory: 4036100 kB  
Disk Subsystem:  
Other Hardware:

## Software

Operating System: Linux 5.1.16-200.fc29.x86\_64  
Compiler: gcc version 12.0.0 20210625 (experimental) (GCC)  
File System:  
System State: multiuser

## Notes/Tuning Information

Base flags: -O2 -mtune=generic -m32  
Peak flags: -Ofast -flto -m32

## Errors

'reportable' flag not set during run