

# CFP2000 Result

Copyright ©1999-2000, Standard Performance Evaluation Corporation

SPECfp2000 = 2065

SPECfp\_base2000 = 1725

SPEC license #00407 Tested by: Vladimir Makarov Test date: Jun 27, 2021 Hardware Avail: Now Software Avail: Now

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	96.1	1664	76.4	2095	
171.swim	3100	129	2402	138	2243	
172.mgrid	1800	170	1059	147	1227	
173.applu	2100	158	1328	159	1317	
177.mesa	1400	116	1206	65.0	2154	
178.galgel	2900	69.8	4156	61.9	4684	
179.art	2600	42.9	6065	35.2	7384	
183.quake	1300	63.1	2059	60.1	2163	
187.facerec	1900	111	1711	65.8	2889	
188.amp	2200	150	1470	135	1631	
189.lucas	2000	124	1619	106	1888	
191.fma3d	2100	146	1436	124	1687	
200.sixtrack	1100	154	716	113	970	
301.apsi	2600	186	1398	181	1435	

## Hardware

CPU: Genuine Intel(R) CPU @ 2.66GHz  
CPU MHz: 2666.489  
FPU: Integrated  
CPU(s) enabled: 4  
CPU(s) orderable: No  
Parallel: No  
Primary Cache:  
Secondary Cache: 4096 KB  
L3 Cache:  
Other Cache:  
Memory: 4036100 kB  
Disk Subsystem:  
Other Hardware:

## Software

Operating System: Linux 5.1.16-200.fc29.x86\_64  
Compiler: gcc version 12.0.0 20210627 (experimental) (GCC)  
File System:  
System State: multiuser

## Notes/Tuning Information

Base flags: -O2 -mtune=generic -m32  
Peak flags: -Ofast -flto -m32

## Errors

'reportable' flag not set during run