

# CFP2000 Result

Copyright ©1999-2000, Standard Performance Evaluation Corporation

SPECfp2000 = 2067

SPECfp\_base2000 = 1726

SPEC license #00407 Tested by: Vladimir Makarov Test date: Jun 30, 2021 Hardware Avail: Now Software Avail: Now

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	95.8	1670	76.4	2096	
171.swim	3100	129	2402	138	2246	
172.mgrid	1800	170	1060	147	1228	
173.applu	2100	158	1329	160	1315	
177.mesa	1400	116	1207	64.3	2178	
178.galgel	2900	69.7	4159	62.1	4668	
179.art	2600	42.8	6077	35.5	7325	
183.quake	1300	63.2	2058	60.1	2162	
187.facerec	1900	111	1713	65.7	2893	
188.amp	2200	149	1475	135	1629	
189.lucas	2000	124	1617	106	1885	
191.fma3d	2100	147	1433	124	1687	
200.sixtrack	1100	153	718	112	981	
301.apsi	2600	186	1399	180	1441	

## Hardware

CPU: Genuine Intel(R) CPU @ 2.66GHz  
CPU MHz: 2666.404  
FPU: Integrated  
CPU(s) enabled: 4  
CPU(s) orderable: No  
Parallel: No  
Primary Cache:  
Secondary Cache: 4096 KB  
L3 Cache:  
Other Cache:  
Memory: 4036100 kB  
Disk Subsystem:  
Other Hardware:

## Software

Operating System: Linux 5.1.16-200.fc29.x86\_64  
Compiler: gcc version 12.0.0 20210630 (experimental) (GCC)  
File System:  
System State: multiuser

## Notes/Tuning Information

Base flags: -O2 -mtune=generic -m32  
Peak flags: -Ofast -flto -m32

## Errors

'reportable' flag not set during run