

# CFP2000 Result

Copyright ©1999-2000, Standard Performance Evaluation Corporation

SPECfp2000 = 2067

SPECfp\_base2000 = 1727

SPEC license #00407 Tested by: Vladimir Makarov Test date: Jul 07, 2021 Hardware Avail: Now Software Avail: Now

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	95.8	1671	76.2	2099	
171.swim	3100	129	2402	138	2242	
172.mgrid	1800	170	1060	147	1228	
173.applu	2100	158	1329	160	1315	
177.mesa	1400	116	1204	65.1	2152	
178.galgel	2900	69.9	4151	62.0	4677	
179.art	2600	42.5	6117	34.9	7442	
183.equake	1300	63.2	2057	60.1	2164	
187.facerec	1900	111	1716	65.8	2885	
188.amp	2200	149	1473	135	1632	
189.lucas	2000	124	1617	106	1889	
191.fma3d	2100	146	1437	125	1677	
200.sixtrack	1100	153	720	112	981	
301.apsi	2600	186	1397	181	1438	

## Hardware

CPU: Genuine Intel(R) CPU @ 2.66GHz  
CPU MHz: 2666.430  
FPU: Integrated  
CPU(s) enabled: 4  
CPU(s) orderable: No  
Parallel: No  
Primary Cache:  
Secondary Cache: 4096 KB  
L3 Cache:  
Other Cache:  
Memory: 4036100 kB  
Disk Subsystem:  
Other Hardware:

## Software

Operating System: Linux 5.1.16-200.fc29.x86\_64  
Compiler: gcc version 12.0.0 20210707 (experimental) (GCC)  
File System:  
System State: multiuser

## Notes/Tuning Information

Base flags: -O2 -mtune=generic -m32  
Peak flags: -Ofast -flto -m32

## Errors

'reportable' flag not set during run