

SPEC® CPU2017 Integer Speed Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

(Test Sponsor: Red Hat, Inc.)


~~SPECspeed2017_int_base = 6.96~~

~~SPECspeed2017_int_peak = 8.50~~

CPU2017 License: 0002991

Test Sponsor: Red Hat, Inc.

Tested by: Vladimir Makarov



Hardware

CPU Name: Intel(R) Core(TM) i7-8700K CPU @ 3.70GHz
 Max MHz.: 3007.104
 Nominal: 3007.104
 Enabled: 6 cores, 1 chip, threads/core
 Orderable:
 Cache L1:
 L2: 12288 KB
 L3:
 Other:
 Memory: 16300620 KB
 Storage: 192 GB add more disk info here
 Other:

Software

OS: Linux 4.17.3-200.fc28.x86_64
 Compiler: 4.17.3-200.fc28.x86_64
 Parallel: gcc version 12.0.0 20210709 (experimental) (GCC)
 Firmware:
 File System: ext4
 System State: multiuser
 Base Pointers: 64-bit
 Peak Pointers: 64-bit
 Other:

Errors

'reportable' flag not set during run
 620.omnetpp_s (base) had invalid runs!
 620.omnetpp_s (peak) had invalid runs!
 Run of 620.omnetpp_s (peak) was not valid; status is RE
 Run of 620.omnetpp_s (base) was not valid; status is RE

(Continued on next page)

SPEC CPU2017 Integer Speed Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

(Test Sponsor: Red Hat, Inc.)

~~SPECspeed2017_int_base = 6.96~~

~~SPECspeed2017_int_peak = 8.50~~

CPU2017 License: 0002991

Test Sponsor: Red Hat, Inc.

Tested by: Vladimir Makarov

~~Test Date: Jul-2021~~

~~Hardware Availability: Now~~

~~Software Availability:~~

Errors (Continued)

Unknown flags were used! See

<https://www.spec.org/cpu2017/Docs/runcpu.html#flagsurl>

for information about how to get rid of this error.

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
600.perlbench_s	4	<u>230</u>	<u>7.70</u>	230	7.71	231	7.69	4	222	8.01	<u>221</u>	<u>8.04</u>	221	8.05
602.gcc_s	4	<u>374</u>	<u>10.6</u>	373	10.7	374	10.6	4	<u>339</u>	<u>11.7</u>	340	11.7	338	11.8
605.mcf_s	4	529	8.92	<u>530</u>	<u>8.92</u>	532	8.88	4	462	10.2	458	10.3	<u>462</u>	<u>10.2</u>
620.omnetpp_s	4	0.00354	0.00	0.0155	0.00	0.00884	0.00	4	0.00966	0.00	0.00987	0.00	0.0151	0.00
623.xalancbmk_s	4	236	6.00	<u>237</u>	<u>5.97</u>	240	5.90	4	219	6.48	224	6.33	<u>223</u>	<u>6.36</u>
625.x264_s	4	312	5.65	<u>313</u>	<u>5.64</u>	314	5.62	4	152	11.6	152	11.6	<u>152</u>	<u>11.6</u>
631.deepsjeng_s	4	299	4.80	297	4.83	<u>297</u>	<u>4.82</u>	4	<u>259</u>	<u>5.54</u>	259	5.54	259	5.54
641.leela_s	4	368	4.64	<u>368</u>	<u>4.64</u>	367	4.64	4	316	5.40	<u>316</u>	<u>5.39</u>	316	5.39
648.exchange2_s	4	316	9.31	<u>317</u>	9.28	<u>317</u>	<u>9.28</u>	4	207	14.2	<u>207</u>	<u>14.2</u>	206	14.3
657.xz_s	4	822	7.52	<u>821</u>	<u>7.53</u>	820	7.54	4	<u>806</u>	<u>7.67</u>	806	7.67	806	7.67
SPECspeed2017_int_base = <u>6.96</u>														
SPECspeed2017_int_peak = <u>8.50</u>														

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

Environment variables set by runcpu before the start of the run:

LD_LIBRARY_PATH = "/notnfs/vmakarov/perf/sbox/gcc/local.spec2017.x86_64/inst.ton8/lib64:/notnfs/vmakarov/perf/sbox/gcc/local.spec2017.x86_64/inst.ton8/lib:/usr/lib64:/usr/lib:/lib64"

Platform Notes

Sysinfo program /notnfs/vmakarov/spec2017/bin/sysinfo
Rev: r5797 of 2017-06-14 96c45e4568ad54c135fd618bcc091c0f
running on ton8 Fri Jul 9 21:45:20 2021

SUT (System Under Test) info as seen by some common utilities.

For more information on this section, see

<https://www.spec.org/cpu2017/Docs/config.html#sysinfo>

From /proc/cpuinfo

model name : Intel(R) Core(TM) i7-8700K CPU @ 3.70GHz

1 "physical id"s (chips)

6 "processors"

cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)

cpu cores : 6

siblings : 6

(Continued on next page)

SPEC CPU2017 Integer Speed Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

(Test Sponsor: Red Hat, Inc.)

~~SPECspeed2017_int_base = 6.96~~

~~SPECspeed2017_int_peak = 8.50~~

CPU2017 License: 0002991

Test Sponsor: Red Hat, Inc.

Tested by: Vladimir Makarov

~~Test Date: Jul-2021~~

~~Hardware Availability: Now~~

~~Software Availability:~~

Platform Notes (Continued)

physical 0: cores 0 1 2 3 4 5

From lscpu:

Architecture: x86_64
CPU op-mode(s): 32-bit, 64-bit
Byte Order: Little Endian
CPU(s): 6
On-line CPU(s) list: 0-5
Thread(s) per core: 1
Core(s) per socket: 6
Socket(s): 1
NUMA node(s): 1
Vendor ID: GenuineIntel
CPU family: 6
Model: 158
Model name: Intel(R) Core(TM) i7-8700K CPU @ 3.70GHz
Stepping: 10
CPU MHz: 4702.287
CPU max MHz: 4700.0000
CPU min MHz: 800.0000
BogoMIPS: 7592.00
Virtualization: VT-x
L1d cache: 32K
L1i cache: 32K
L2 cache: 256K
L3 cache: 12288K
NUMA node0 CPU(s): 0-5
Flags: fpu vme de pse tsc msr pae cx8 apic sep mtrr pge mca cmov pat pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx pdpe1gb rdtscp lm constant_tsc art arch_perfmon pebs bts rep_good nopl xtopology nonstop_tsc cpuid aperf mperf tsc_known_freq pni pclmulqdq dtes64 monitor ds_cpl vmx smx est tm2 ssse3 sdbg fma cx16 xtpr pdcm pcid sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer aes xsave avx f16c rdrand lahf_lm abm 3dnowprefetch cpuid_fault invpcid_single ptibr ibpb stibp tpr_shadow vnmi flexpriority ept vpid fsgsbase tsc_adjust bmi1 hle avx2 smep bmi2 erms invpcid rtm mpx rdseed adx smap clflushopt intel_pt xsaveopt xsavec xgetbv1 xsaves dtherm ida arat pln pts hwp hwp_notify hwp_act_window hwp_epp

/proc/cpuinfo cache data
cache size : 12288 KB

From numactl --hardware WARNING: a numactl 'node' might or might not correspond to a physical chip.

From /proc/meminfo

MemTotal: 16300620 kB
HugePages_Total: 0
Hugepagesize: 2048 kB

(Continued on next page)

SPEC CPU2017 Integer Speed Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

(Test Sponsor: Red Hat, Inc.)

~~SPECspeed2017_int_base = 6.96~~

~~SPECspeed2017_int_peak = 8.50~~

CPU2017 License: 0002991

Test Sponsor: Red Hat, Inc.

Tested by: Vladimir Makarov

~~Test Date: Jul-2021~~

~~Hardware Availability: Now~~

~~Software Availability:~~

Platform Notes (Continued)

```
From /etc/*release* /etc/*version*
fedora-release: Fedora release 28 (Twenty Eight)
os-release:
  NAME=Fedora
  VERSION="28 (Workstation Edition)"
  ID=fedora
  VERSION_ID=28
  PLATFORM_ID="platform:f28"
  PRETTY_NAME="Fedora 28 (Workstation Edition)"
  ANSI_COLOR="0;34"
  CPE_NAME="cpe:/o:fedoraproject:fedora:28"
redhat-release: Fedora release 28 (Twenty Eight)
system-release: Fedora release 28 (Twenty Eight)
system-release-cpe: cpe:/o:fedoraproject:fedora:28
```

uname -a:

```
Linux ton8 4.17.3-200.fc28.x86_64 #1 SMP Tue Jun 26 14:17:07 UTC 2018 x86_64 x86_64
x86_64 GNU/Linux
```

SPEC is set to: /notnfs/vmakarov/spec2017

Filesystem	Type	Size	Used	Avail	Use%	Mounted on
/dev/mapper/fedora-home	ext4	192G	47G	136G	26%	/notnfs

Additional information from dmidecode follows. WARNING: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

(End of data from sysinfo program)

Compiler Version Notes

```
=====
CXXC 620.omnetpp_s(base, peak) 623.xalancbmk_s(base, peak)
  631.deepsjeng_s(base, peak) 641.leela_s(base, peak)
-----
```

Using built-in specs.

COLLECT_GCC=/notnfs/vmakarov/perf/sbox/gcc/local.spec2017.x86_64/inst.ton8/bin/g++

COLLECT_LTO_WRAPPER=/notnfs/vmakarov/perf/sbox/gcc/local.spec2017.x86_64/inst.ton8/libexec/gcc/x86_64-pc-linux-gnu/12.0.0/lto-wrapper

Target: x86_64-pc-linux-gnu

Configured with:

```
/notnfs/vmakarov/perf/sbox/gcc/local.spec2017.x86_64/src/configure
--prefix=/notnfs/vmakarov/perf/sbox/gcc/local.spec2017.x86_64/inst.ton8
--srcdir=/notnfs/vmakarov/perf/sbox/gcc/local.spec2017.x86_64/src
```

(Continued on next page)

SPEC CPU2017 Integer Speed Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

(Test Sponsor: Red Hat, Inc.)

~~SPECspeed2017_int_base = 6.96~~

~~SPECspeed2017_int_peak = 8.50~~

CPU2017 License: 0002991

Test Sponsor: Red Hat, Inc.

Tested by: Vladimir Makarov

~~Test Date: Jul-2021~~

~~Hardware Availability: Now~~

~~Software Availability:~~

Compiler Version Notes (Continued)

```
--disable-bootstrap --disable-libcilkrts --enable-checking=release
--enable-languages=c,c++,fortran
Thread model: posix
Supported LTO compression algorithms: zlib
gcc version 12.0.0 20210709 (experimental) (GCC)
-----
=====
CC 600.perlbench_s(base, peak) 602.gcc_s(base, peak) 605.mcf_s(base, peak)
625.x264_s(base, peak) 657.xz_s(base, peak)
-----
Using built-in specs.
COLLECT_GCC=/notnfs/vmakarov/perf/sbox/gcc/local.spec2017.x86_64/inst.ton8/bin/gcc
COLLECT_LTO_WRAPPER=/notnfs/vmakarov/perf/sbox/gcc/local.spec2017.x86_64/inst.ton8/libexec/gcc/x86_64-pc-linux-gnu/12.0.0/lto-wrapper
Target: x86_64-pc-linux-gnu
Configured with:
/notnfs/vmakarov/perf/sbox/gcc/local.spec2017.x86_64/src/configure
--prefix=/notnfs/vmakarov/perf/sbox/gcc/local.spec2017.x86_64/inst.ton8
--srcdir=/notnfs/vmakarov/perf/sbox/gcc/local.spec2017.x86_64/src
--disable-bootstrap --disable-libcilkrts --enable-checking=release
--enable-languages=c,c++,fortran
Thread model: posix
Supported LTO compression algorithms: zlib
gcc version 12.0.0 20210709 (experimental) (GCC)
-----
=====
FC 648.exchange2_s(base, peak)
-----
Using built-in specs.
COLLECT_GCC=/notnfs/vmakarov/perf/sbox/gcc/local.spec2017.x86_64/inst.ton8/bin/gfortran
COLLECT_LTO_WRAPPER=/notnfs/vmakarov/perf/sbox/gcc/local.spec2017.x86_64/inst.ton8/libexec/gcc/x86_64-pc-linux-gnu/12.0.0/lto-wrapper
Target: x86_64-pc-linux-gnu
Configured with:
/notnfs/vmakarov/perf/sbox/gcc/local.spec2017.x86_64/src/configure
--prefix=/notnfs/vmakarov/perf/sbox/gcc/local.spec2017.x86_64/inst.ton8
--srcdir=/notnfs/vmakarov/perf/sbox/gcc/local.spec2017.x86_64/src
--disable-bootstrap --disable-libcilkrts --enable-checking=release
--enable-languages=c,c++,fortran
Thread model: posix
Supported LTO compression algorithms: zlib
gcc version 12.0.0 20210709 (experimental) (GCC)
```

SPEC CPU2017 Integer Speed Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

(Test Sponsor: Red Hat, Inc.)

~~SPECspeed2017_int_base = 6.96~~

~~SPECspeed2017_int_peak = 8.50~~

CPU2017 License: 0002991

Test Sponsor: Red Hat, Inc.

Tested by: Vladimir Makarov

~~Test Date: Jul-2021~~

~~Hardware Availability: Now~~

~~Software Availability:~~

Base Unknown Flags

600.perlbench_s: "-fcommonARRAY(0x9f56ca0) "-fcommonARRAY(0x9f6c790)

602.gcc_s: "-fcommonARRAY(0x9f54010) "-fcommonARRAY(0x9f93e98)

605.mcf_s: "-fcommonARRAY(0x9f73f50) "-fcommonARRAY(0x9fc5148)

620.omnetpp_s: "-fcommonARRAY(0x9f6f520) "-fcommonARRAY(0xa0ef118)

623.xalancbmk_s: "-fcommonARRAY(0x9f64970) "-fcommonARRAY(0xa0efd10)

625.x264_s: "-fcommonARRAY(0x9f6ccd0) "-fcommonARRAY(0xa0f0488)

631.deepsjeng_s: "-fcommonARRAY(0x9fa6780) "-fcommonARRAY(0xa0f0848)

641.leela_s: "-fcommonARRAY(0x9ff9868) "-fcommonARRAY(0xa0f0f20)

648.exchange2_s: "-fallow-argument-mismatchARRAY(0xa0ef890)

"-fallow-argument-mismatchARRAY(0xa109630)

657.xz_s: "-fcommonARRAY(0xa0effe0) "-fcommonARRAY(0xa084d10)

Peak Unknown Flags

600.perlbench_s: "-fcommonARRAY(0x9f56ca0) "-fcommonARRAY(0x9f6c790)

602.gcc_s: "-fcommonARRAY(0x9f54010) "-fcommonARRAY(0x9f93e98)

605.mcf_s: "-fcommonARRAY(0x9f73f50) "-fcommonARRAY(0x9fc5148)

620.omnetpp_s: "-fcommonARRAY(0x9f6f520) "-fcommonARRAY(0xa0ef118)

623.xalancbmk_s: "-fcommonARRAY(0x9f64970) "-fcommonARRAY(0xa0efd10)

625.x264_s: "-fcommonARRAY(0x9f6ccd0) "-fcommonARRAY(0xa0f0488)

631.deepsjeng_s: "-fcommonARRAY(0x9fa6780) "-fcommonARRAY(0xa0f0848)

641.leela_s: "-fcommonARRAY(0x9ff9868) "-fcommonARRAY(0xa0f0f20)

648.exchange2_s: "-fallow-argument-mismatchARRAY(0xa0ef890)

"-fallow-argument-mismatchARRAY(0xa109630)

657.xz_s: "-fcommonARRAY(0xa0effe0) "-fcommonARRAY(0xa084d10)

(Continued on next page)

SPEC CPU2017 Integer Speed Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

(Test Sponsor: Red Hat, Inc.)

~~SPECspeed2017_int_base = 6.96~~

~~SPECspeed2017_int_peak = 8.50~~

CPU2017 License: 0002991

Test Sponsor: Red Hat, Inc.

Tested by: Vladimir Makarov

~~Test Date: Jul-2021~~

~~Hardware Availability: Now~~

~~Software Availability:~~

Peak Unknown Flags (Continued)

600.perlbench_s: "-fcommonARRAY(0xa0f0920) "-fcommonARRAY(0xa121b70)
"-fltoARRAY(0xa136990)

602.gcc_s: "-fcommonARRAY(0xa0f1f68) "-fcommonARRAY(0xa130288)
"-fltoARRAY(0xa123690)

605.mcf_s: "-fcommonARRAY(0xa11b498) "-fcommonARRAY(0xa12b330)
"-fltoARRAY(0xa087020)

620.omnetpp_s: "-fcommonARRAY(0xa0eed10) "-fcommonARRAY(0xa132728)
"-fltoARRAY(0xa138fc0)

623.xalancbmk_s: "-fcommonARRAY(0xa136858) "-fcommonARRAY(0xa12a7f0)
"-fltoARRAY(0xa136f90)

625.x264_s: "-fcommonARRAY(0xa1371e8) "-fcommonARRAY(0xa1236f0)
"-fltoARRAY(0xa138d98)

631.deepsjeng_s: "-fcommonARRAY(0xa132860) "-fcommonARRAY(0xa121ed0)
"-fltoARRAY(0xa1408a8)

641.leela_s: "-fcommonARRAY(0xa12d058) "-fcommonARRAY(0xa138bd0)
"-fltoARRAY(0xa1413b8)

648.exchange2_s: "-fallow-argument-mismatchARRAY(0xa12a718)
"-fallow-argument-mismatchARRAY(0xa13bde8)
"-fltoARRAY(0xa141ef0)

657.xz_s: "-fcommonARRAY(0xa124080) "-fcommonARRAY(0xa1411f0)
"-fltoARRAY(0xa142a28)

Base Compiler Invocation

C benchmarks:
gcc

C++ benchmarks:
g++

Fortran benchmarks:
gfortran

SPEC CPU2017 Integer Speed Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

(Test Sponsor: Red Hat, Inc.)

~~SPECspeed2017_int_base = 6.96~~

~~SPECspeed2017_int_peak = 8.50~~

CPU2017 License: 0002991

Test Sponsor: Red Hat, Inc.

Tested by: Vladimir Makarov

~~Test Date: Jul-2021~~

~~Hardware Availability: Now~~

~~Software Availability:~~

Base Portability Flags

600.perlbench_s: -DSPEC_LINUX_X64 -DSPEC_LP64
602.gcc_s: -DSPEC_LP64
605.mcf_s: -DSPEC_LP64
620.omnetpp_s: -DSPEC_LP64
623.xalancbmk_s: -DSPEC_LINUX -DSPEC_LP64
625.x264_s: -DSPEC_LP64
631.deepsjeng_s: -DSPEC_LP64
641.leela_s: -DSPEC_LP64
648.exchange2_s: -DSPEC_LP64
657.xz_s: -DSPEC_LP64

Base Optimization Flags

C benchmarks:

-z muldefs -O2 -mtune=generic -fopenmp -DSPEC_OPENMP -fgnu89-inline
-fno-strict-aliasing

C++ benchmarks:

-O2 -mtune=generic -fopenmp -DSPEC_OPENMP

Fortran benchmarks:

-O2 -mtune=generic -DSPEC_OPENMP -fopenmp

Peak Compiler Invocation

C benchmarks:

gcc

C++ benchmarks:

g++

Fortran benchmarks:

gfortran

Peak Portability Flags

Same as Base Portability Flags

SPEC CPU2017 Integer Speed Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

(Test Sponsor: Red Hat, Inc.)

~~SPECspeed2017_int_base = 6.96~~

~~SPECspeed2017_int_peak = 8.50~~

CPU2017 License: 0002991

Test Sponsor: Red Hat, Inc.

Tested by: Vladimir Makarov

~~Test Date: Jul-2021~~

~~Hardware Availability: Now~~

~~Software Availability:~~

Peak Optimization Flags

C benchmarks:

~~-z muldefs -Ofast -mtune=corei7 -march=core-avx2 -fopenmp
-DSPEC_OPENMP -fgnu89-inline -fno-strict-aliasing~~

C++ benchmarks:

~~-Ofast -mtune=corei7 -march=core-avx2 -fopenmp -DSPEC_OPENMP~~

Fortran benchmarks:

~~-Ofast -mtune=corei7 -march=core-avx2 -DSPEC_OPENMP -fopenmp~~

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU2017 v1.0.1 on 2021-07-09 21:45:20-0400.

Report generated on 2021-07-10 03:11:42 by CPU2017 PDF formatter v5748.